



NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE ∅0.46mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOMHS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50HZ 1MIN.

MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.STORAGE :-40°~+85°T
- 2.OPERATION :0° TO 70° C.

PC Board Layout

Component Side Shown

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:
CHECKED:	DATE:
DRAWN:	DATE:
SXA	2019-06-21

<p><b>C</b> 深圳市灿科盟实业有限公司 kmtw CHANKEMENG INDUSTRYCO., LTD</p>	
TITLE:	R-RJ45R08P-A012
CLIENT P/N	R-RJ45R08P-A012
UNIT	mm
SCALE	free
FILE NO.	Ckmtw-RJ45-0198
REV.	A
HY04	