



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

- 1.HOUSING MATERIAL
- 2.CONTACT MATERIAL
- 3.PLATING
- 4.SHIELD
- 5.LED

ELECTRICAL:

- 1.VOLTAGE RATING
- 2.CURRENT RATING
- 3.CONTACT RESISTANCE
- 4.INSULATION RESISTANCE
- 5.DIELECTRIC WITHSTANDING RESISTANCE

MECHANICAL:

- 1.DURABILITY
- 2.PCB RETENTION PRE-SOLDER

ENVIRONMENTAL:

- 1.STORAGE
- 2.OPERATION

- :GLASS FILLED POLYESTER UL94V-0.
- :PHOSPHOR BRONZE Ø0.46mm
- :GOLD PLATING OVER NICKEL.
- :0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.
- :OPTION

- :125 VAC RMS.
- :15 AMP.
- :30 MILLIOHMS MAX.
- :500 MEGOHMS MIN @ 500V DC.
- :1000V AC RMS 50Hz 1MIN.

- :750 CYCLES MIN.
- :1 LB MIN.

- : -40°~+85°
- : 0° TO 70° C

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED: DATE:

CHECKED: DATE:

DRAWN: DATE:

L. YUN 2020-05-28

深圳市灿科盟实业有限公司
Ckmtw CHANKLEMENT INDUSTRYCO., LTD

TITLE:

RJ45-8P/8C 2*2 四胞胎 弯脚 带屏蔽 带灯带弹片
(5JB-2X2-8P8C-LED-S-E)

P/N	R-RJ45R08P-C402
UNIT	mm
SCALE	Free
FILE NO.	Ckmtw-RJ45-0238
REV.	A
	HY04