



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
 - 2 CONTACT MATERIAL
 - 3 PLATING
 - 4 SHIELD
- ELECTRICAL:
- 1 VOLTAGE RATING
 - 2 CURRENT RATING
 - 3 CONTACT RESISTANCE
 - 4 INSULATION RESISTANCE
 - 5 DIELECTRIC WITHSTANDING RESISTANCE
- MECHANICAL:
- 1 DURABILITY
 - 2 PCB RETENTION PRE-SOLDER
- ENVIRONMENTAL:
- 1 STORAGE
 - 2 OPERATION

- 125 VAC RMS
- 15 AMP
- 30 MILLIOHMS MAX.
- 500 MEGOHMS MIN @ 500V DC
- 1000V AC RMS 50HZ MIN
- 750 CYCLES MIN
- 1 LB MIN
- 40°C~+85°C
- 0°C TO 70°C

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE: RJ45-8P/8C 2*4P 八胞胎 弯插 带屏蔽 带灯 带弹片 (5JB-2X4-8P8C-LED-S-E)
ZYJ	2016-10-19	PART. NO. R-RJ45R08P-C802
		UNIT mm
		SCALE Free
		FILE NO. Ckmtw-RJ45-0113
		REV. A
		HY04